

WHEELGUIDES, RUBBER BUMPERS AND PROTECTION POSTS



Truck guides

The truck guides enable drivers to appropriately position the truck against the dock, thus preventing the shelters, bays or other facilities from being damaged due to an incorrect approach by the truck.

Models available: G-25 (with chock angle). Length 2500mm; G-15 (straight). Length 1500mm; (for building in or bolting to the ground).

Finishes: primer, painted black, yellow or galvanised; GH 3000 (Concrete). Length 3000mm, weight 450 Kg/each.

Dock bumpers (proportional, according to measurements)

The protection stops prevent the truck from hitting the levelling ramp and for ensuring the required distance is kept between the truck and the ramp to guarantee the correct working order of the levelling ramp during the loading and unloading process.



Mod. **TMA 490**
490x150x55 mm.
Material:
Metal strip +
rubber + metal plate



Mod. **TMA 600**
600x200x150 mm.
TMA 800
800x200x150 mm.
Material:
Metal strip +
rubber + metal plate



Mod. **TC 400**
405x70x80 mm.
Material:
Polyurethane
+ built-in
metal plate



Mod. **TC 450**
450x250x115 mm.
Material:
Rubber +
10 mm.
metal plate.



Mod. **TR 400**
400x110x115 mm.
Material:
3 rubber rollers
+ galvanised U-profile



Mod. **TM500**
500x300x125 mm.
Material:
2 overlapping 10/8mm metal
U-profiles with elastic inner
parts
(for impact absorption).
Zinc-plated or painted.

Protection posts (Protect against accidental knocks).



Mod. **C-LAGRIMADA**
400x400x300 mm.
Mod. **C-LAGRIMADA**
500x400x300 mm.
Mod. **C-LAGRIMADA**
800x400x300 mm.
(Yellow or zinc)



Mod. **E-TRIANGULAR**
400x170x120 mm.
(Yellow and black)



Mod. **BELL**
440x300x300 mm.
(Yellow or zinc)



Mod. **TUBULAR DELTA**
800x400x240 mm.
(Yellow or zinc)



Mod. **AUTOREPARABLE D100**
polymeric composite
Ø 100mm. Height 900mm

Height x width x depth